

AMENDMENTS TO THE SPECIFICATION

Please replace the paragraph beginning on page 13, line 1, which starts with the following amended paragraph:

A plurality of arcuate feet 101, preferably at least two, may be provided and attached to the housing 91 to provide resistance to rolling of the cylindrical housing. A handle ~~[[98]]~~ 103 may also be provided to facilitate lifting and carrying.

Please replace the paragraph beginning on page 13, line 4, which starts with the following amended paragraph:

The pump device 20 applies a negative pressure, commonly called a vacuum, to the urine holding container 12 via the second conduit 16 as described above. The negative pressure induced by the pump 81 of the pump device 20 draws urine from the first collection chamber or reservoir 19 of urinal 10 into the reservoir 15 of the urinal holding container 12 through the first conduit 14 and through the siphon tube 31 of the pickup 25. Referring now to FIG. 6, the motor 82 is connected to a power source 100 via a first electric connector indicated by numeral ~~[[101]]~~ 83. The power source 100 can be either a battery, a conventional alternating current power supply, a portable generator or the like, or a combination of sources. A non-limiting example of a pump device 20 includes that disclosed in U.S. Patent 5,415,632 issued May 16, 1995 to Ilan Samson and assigned to Playskol, Inc., which disclosure is incorporated herein by reference. Another non-limiting example includes the pump device disclosed in U.S. Patent 6,129,699 issued on October 10, 2000 to Levoy G. Haight et al. and assigned to Sorenson Development, Inc. which disclosure is incorporated herein by reference.